The Mathematical Problem of Hydrodynamic Stability*

D. H. SATTINGER

Communicated by E. Hopf

1. Introduction. The Navier-Stokes equations governing viscous incompressible flow are

(1.1)
$$\partial_i u_i + u_i \partial_i u_i = -\partial_i p + \frac{1}{R} \Delta u_i,$$

$$\partial_i u_i = 0.$$

where $\partial_i = \partial/\partial x_i$, $\partial_t = \partial/\partial_t$, and repeated indices denote summation. The functions u_i , i = 1, 2, 3, are the components of the velocity field in rectilinear coordinates, and p denotes the pressure. The quantities in (1.1) are non-dimensional. The parameter R is called the Reynolds number for the flow and is a dimensionless quantity.

Let D be a bounded region of \mathbb{R}^3 with boundary ∂D . Due to the viscosity, the fluid must adhere to the walls of D. If the boundaries are moving at a constant, tangential rate (such as a sphere or cylinder rotating about its axis of symmetry) then the fluid must move with the walls at the boundary. Let \bar{u} be a stationary (time independent) solution of (1.1) satisfying non-homogeneous boundary conditions. An interesting question, and one which has occupied an important position in the research of experimentalists and applied mathematicians, is that of the *stability* of the flow \bar{u} . That is, if the flow is disturbed slightly, do the perturbations grow or decay? If the solution of (1.1) is written in the form $u = \bar{u} + v$, where v denotes the perturbed flow, then we derive for v the system of equations

(1.2)
$$\partial_i v_i + v_i \ \partial_i v_i + \tilde{u}_i \ \partial_i v_i + v_j \ \partial_i \tilde{u}_i = -\partial_i p + \frac{1}{R} \Delta v_i,$$

$$\partial_i v_i = 0, \quad v_i = 0 \quad \text{on} \quad \partial D.$$

^{*} The preparation of this paper was sponsored in part by the Office of Naval Research under Contract NONR 233(76). Reproduction in whole or in part is permitted for any purpose of the United States Government.