## Inequalities for Integral Bilinear Forms with Applications to Mechanical Systems

## THOMAS E. VOLLMAN

1. Introduction. The results presented in this paper are motivated by the following considerations. If K(x, t) is the Green's function of a one dimensional mechanical system, then the transverse displacement due to a distributed load, p(x),  $x \in [0, 1]$ , is given by

$$u(x) = \int_0^1 K(x, t)p(t)dt.$$

The potential energy of the system is then given by

(1.1) 
$$E(K, p) = \int_{0}^{1} \int_{0}^{1} K(x, t)p(x)p(t)dx dt,$$

(see [4]).

The problem to be considered in this paper is that of finding extreme values of this energy when the load p is restricted to be in a given class of functions. The main classes to be considered here will be the classes of equimeasureable functions on [0, 1]. Two functions, f and g, are said to be equimeasureable if for every real number y, the sets  $\{x|f(x) \ge y\}$  and  $\{x|g(x) \ge y\}$  have the same measure.

Following Hardy, Littlewood and Polya [7] we define the rearrangement  $\bar{f}$ , of a nonnegative, integrable function on (0, 1) in increasing order as follows. Let M(y) denote the measure of the set  $\{x|f(x) \leq y\}$  and define  $\bar{f}$  at x = M(y) to be  $\bar{f}(x) = y$ . We note that  $\bar{f}$  is an increasing function of x, defined uniquely on (0, 1) except for at most an enumerable set of values of x, viz. those corresponding to intervals of constancy of M(y). We may complete the definition of  $\bar{f}(x)$  by agreeing that at a point of discontinuity, we have

$$\bar{f}(x) = \frac{1}{2} \{ \bar{f}(x-0) + \bar{f}(x+0) \}.$$

We now define the rearrangement of f in symmetrically decreasing order, f, as follows:

$$\hat{f}(x) = \bar{f}(2x), x \in [0, \frac{1}{2}]$$
 and  $\hat{f}(x) = \hat{f}(1-x), x \in [\frac{1}{2}, 1].$ 

Indiana University Mathematics Journal ©, Vol. 26, No. 5 (1977)