Generalizations of the Inversion Formula of Thin Airfoil Theory*

H. K. CHENG† & N. ROTT

Cornell University, Ithaca, New York

Communicated by M. Kac

1. In the theory of two-dimensional flow of an ideal fluid past a thin airfoil there arise two types of problem, which may be called the "thickness" problem and the "lifting" problem; they lead to two different types of boundary value problem for the complex velocity w = u - iv in the complex plane of flow, z = x + iy. The problem in the "thickness" case is the determination of the flow past a symmetrical airfoil at zero angle of attack, leading to the following mathematical formulation: along a portion of the real axis (the chord: $a_1 \le x \le a_2$, say) values of the velocity component v, equal in magnitude and opposite in directions for the upper and lower sides of the chord, are prescribed: $v(x, +0) = -v(x, -0)(=v_0, \text{ say})$. An analytic function w whose imaginary part satisfies this boundary condition and for which w = 0 at infinity is to be determined. Throughout this paper, the letter w represents only the "disturbance" velocity, which must vanish at infinity. Of special interest is the value of the u-component on the chord, u(x, 0).

Since the boundary condition for v is antisymmetric with respect to the real axis, it is easily recognized that the harmonic function v is itself antisymmetric: v(x, y) = -v(x, -y). It follows that for the portions of the real axis outside the chord we have v(x, 0) = 0. Thus, the problem may be formulated as a boundary value problem for the upper half plane (say), with v given along the whole real axis.

The solution is immediately obtained by distributing along the real axis sources whose strength per unit length equals twice the velocity v_0 on the upper

^{*}This research was supported by the United States Air Force under Contract No. AF 33(038)-21406, monitored by the Office of Scientific Research, Air Research and Development Command.

[†] Now with Bell Aircraft Corp.