Fracture of Circular Pipes by Internal Pressure

T. Y. THOMAS

Contents

1.	Introduction	623
2.	General symmetry and equilibrium conditions	624
3.	Elastic deformation of the pipe	626
4.	Yield condition. Beginning of plastic deformation	629
5.	Plastic deformation of the pipe. Boundary conditions	630
6.	Solution of the plastic equilibrium problem	631
7.	Justification of the tentative yield condition	634
8.	Surface of strong instability. Plastic flow	635
9.	Violation of circular symmetry	636
10.	Fracture in pipes	638

1. Introduction. The occurrence of a small slip of the material particles or discontinuity in the particle velocity over a surface in a solid will, in general, be damped out as a consequence of the boundary conditions and the conditions imposed by the equations governing the behavior of the material. For certain special surfaces, however, the discontinuity will become indefinitely large within a finite time. These latter surfaces, called surfaces of strong instability, have been proposed as surfaces over which the solid will fracture or rupture. On the basis of this criterion we have shown in several previous publications¹ that a plate under uniform tension at the yield point may fracture along the well known Lüders band and correspondingly that a circular bar, stressed uniformly in the direction of its axis, is subject to fracture over a plane perpendicular to the axis or along a circular cone whose axis coincides with the axis of the bar.

This article² deals with the fracture of a circular pipe produced solely by

¹See T. Y. Thomas, Plastic flow and fracture in solids, *Jour. of Math. & Mech.* 7 (1958), pp. 291-322, also Rupture of round bars by tension, *ibid.*, 8 (1959), pp. 1-25.

²This investigation was conducted at the request of the Naval Research Laboratory and has been supported by the Office of Naval Research under Contract Nonr-908(09), Indiana University, NR 041 037.